

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**CLAIMS:**

1. (Cancelled)

2. (Amended)

A flame simulating assembly for providing at least one image of flames, the flame simulating assembly comprising:

at least one light source;

a first screen positioned in a first path of light from said at least one light source, the first screen being adapted to receive light from said at least one light source to form said at least one image of flames transmittable through the first screen;

a second screen positioned in a second path of light from said at least one light source, the second screen being adapted to receive light from said at least one light source to form said at least one image of flames transmittable through the second screen;

~~according to claim 1 in which each of the first screen and the second screen at least partially defined~~defining substantially vertical planes respectively; and

said at least one light source ~~is being~~ positioned substantially between said planes.

3. (Amended)

A flame simulating assembly according to claim 1 ~~2~~ additionally comprising at least one flame effect element for configuring light from said at least one light

source to produce said at least one image of flames, said at least one flame effect element being positioned in said at least one path of light.

4. (Cancelled)

5. (Amended)

A flame simulating assembly according to claim ~~4~~2 additionally comprising at least one flame effect element for configuring light from said at least one light source to produce said at least one image of flames, said at least one flame effect element being positioned in said first path of light between said at least one light source and the first screen and in said second path of light between said at least one light source and the second screen.

6. (Original)

A flame simulating assembly according to claim 5 in which the first screen and the second screen are positioned on opposite sides of said at least one flame effect element.

7. (Withdrawn)

8. (Withdrawn)

9. (Withdrawn)

10. (Withdrawn)

11. (Withdrawn)

12. (Withdrawn)

13. (Withdrawn)

14. (Withdrawn)

15. (Withdrawn)

16. (Withdrawn)

17. (Withdrawn)

18. (Cancelled)

19. (Cancelled)

20. (Amended)

A flame simulating assembly according to claim ~~1~~2 additionally comprising:

a first flicker element for causing light from said at least one light source to fluctuate, for producing a first image of flames transmitted through the first screen, the first flicker element being positioned in said first path of light between said at least one light source and the first screen; and

a second flicker element for causing light from said at least one light source to fluctuate, for producing a second image of flames transmitted through the second screen, the second flicker element being positioned in said second path of light between said at least one light source and the second screen.

21. (Previously presented)

A flame simulating assembly according to claim 20 additionally comprising at least one flame effect element for configuring the fluctuating light to simulate flames, said at least one flame effect element being positioned in the first and second paths of light to form the first and the second images of flames transmittable through the first screen and the second screen respectively.

22. (Cancelled)

23. (Amended)

A flame simulating assembly according to claim 202 additionally comprising a first simulated fuel bed and a second simulated fuel bed positioned adjacent to the first screen and the second screen respectively such that the first image of flames and the second image of flames transmitted through the first and second screens respectively are positioned proximal to the first simulated fuel bed and the second simulated fuel bed respectively.

24. (Previously presented)

A flame simulating assembly for providing at least one image of flames, the flame simulating assembly comprising:

- a first simulated fuel bed;
- a second simulated fuel bed;
- at least one light source;
- a first screen comprising a first front surface and positioned behind the first simulated fuel bed in a first path of light from said at least one light source for transmitting said at least one image of flames through the first front surface proximal to the first simulated fuel bed; and
- a second screen comprising a second front surface and positioned behind the second simulated fuel bed in a second path of light from said at least one light source for transmitting said at least one image of flames through the second front surface proximal to the second simulated fuel bed.

25. (Previously presented)

A flame simulating assembly according to claim 24 additionally comprising at least one flicker element for creating a fluctuating light, said at least one flicker element being positioned in at least one path of light selected from the group consisting of said first path of light and said second path of light, whereby the

fluctuating light forms said at least one image of flames transmittable through the first and the second front surfaces respectively.

26. (Previously presented)

A flame simulating assembly according to claim 25 additionally comprising at least one flame effect element for configuring light from said at least one light source to produce said at least one image of flames, said at least one flame effect element being positioned in said first path of light between said at least one light source and the first screen and in said second path of light between said at least one light source and the second screen.

27. (Previously presented)

A flame simulating assembly according to claim 24 additionally comprising:

a first flicker element for causing light from said at least one light source to fluctuate, for producing a first image of flames transmitted through the first front surface, the first flicker element being positioned in said first path of light between said at least one light source and the first screen; and  
a second flicker element for causing light from said at least one light source to fluctuate, for producing a second image of flames transmitted through the second front surface, the second flicker element being positioned in said second path of light between said at least one light source and the second screen.

28. (Previously presented)

A flame simulating assembly according to claim 27 additionally comprising at least one flame effect element for configuring the fluctuating light to simulate flames, said at least one flame effect element being positioned in the first and second paths of light to form the first and the second images of flames transmittable through the first front surface and the second front surface respectively.

## 29. (Previously presented)

A flame simulating assembly according to claim 28 in which said at least one flame effect element includes:

at least one opening positioned in said second path of light to permit light from said at least one light source to pass through said at least one opening to said second screen; and

at least one reflective region positioned in said first path of light for reflecting light from said at least one light source to said first screen.

## 30. (Previously presented)

A flame simulating assembly according to claim 28 in which said at least one flame effect element comprises at least one opening for configuring light from the light source to simulate flames.

## 31. (Previously presented)

A flame simulating assembly according to claim 28 in which said at least one flame effect element includes a first side facing the first screen and a second side facing the second screen, the second side and the first side being disposed opposite to each other, and in which each of the first and second sides includes a reflective portion for reflecting light from said at least one light source to the first screen and the second screen respectively to produce said first and second images of flames respectively.

## 32. (Previously presented)

A flame simulating assembly according to claim 24 in which at least one of said screens comprises a pattern on the front surface thereof for simulating a firebrick wall positioned adjacent to said at least one image of flames transmitted through said at least one of said screens.

## 33. (Previously presented)

A flame simulating assembly according to claim 24 in which the first front surface and the second front surface are at least partially reflective and in which each of the first screen and the second screen comprises a back surface for diffusing light from said at least one light source and transmitting said at least one image of flames.

34. (Previously presented)

A flame simulating assembly according to claim 33 in which each of the partially reflective front surfaces comprises a substantially non-reflective matte region thereon, each said non-reflective matte region being disposed distal from the first simulated fuel bed and the second simulated fuel bed respectively, each of the screens comprising a portion of the front surface which is a generally reflective region, such that the first simulated fuel bed and the second simulated fuel bed are substantially the only objects reflected in the reflective regions respectively, whereby light from said at least one light source is transmitted through the front surfaces of the screens respectively to produce said at least one image of flames.

35. (Previously presented)

A flame simulating assembly according to claim 34 which each said front surface further comprises a transition region which is partially reflective and partially non-reflective, each said transition region being positioned between each said non-reflective matte region and each said reflective region on each said partially reflective surface on each said screen respectively.

36. (Original)

A flame simulating assembly according to claim 33 in which at least one of the back surfaces of the first screen and the second screen is non-planar such that said at least one image of flames transmitted through said at least one back surface appears to be substantially three-dimensional.

37. (Previously presented)

A flame simulating assembly according to claim 24 additionally comprising at least one reflector positioned in front of at least one of the first simulated fuel bed and the second simulated fuel bed, said at least one reflector being positioned to reflect light from said at least one light source onto said at least one simulated fuel bed to simulate glowing embers.

38. (Previously presented)

A flame simulating assembly according to claim 24 in which each of the first screen and the second screen includes a top region positioned distal from the first simulated fuel bed and the second simulated fuel bed respectively, the top regions being adapted to permit substantially unobstructed observation therethrough.

39. (Previously presented)

A flame simulating assembly according to claim 38 in which each of the top regions is substantially transparent.

40. (Previously presented)

A flame simulating assembly according to claim 38 in which each of the top regions is substantially translucent.

41. (Previously presented)

A flame simulating assembly according to claim 24 additionally including a frame and in which each of the first screen and the second screen is positioned within the frame to maintain the screens in substantially upright positions, each of the first screen and the second screen including a top edge distal from the first simulated fuel bed and the second simulated fuel bed respectively, the top edges of the screens being spaced apart from an upper portion of the frame to define upper openings formed in the flame simulating assembly to permit substantially unobstructed observation therethrough.

42. (Previously presented)



A flame simulating assembly comprising:

- a first simulated fuel bed;
- a second simulated fuel bed;
- at least one light source;
- at least one flicker element positioned in a path of light from the light source, for creating a fluctuating light;
- a first screen positioned behind the first simulated fuel bed for transmitting the fluctuating light; and
- a second screen positioned behind the second simulated fuel bed for transmitting the fluctuating light,

whereby the fluctuating light is transmitted through the first screen and the second screen to simulate flames appearing above the first simulated fuel bed and the second simulated fuel bed respectively.

43. (Amended)

A flame simulating assembly for providing at least one image of flames, the flame simulating assembly comprising:

- at least one light source;
- a first screen having a first front surface and an opposed first back surface;
- a second screen having a second front surface and an opposed second back surface;
- the first and second screens being disposed relative to each other such that the first and the second front surfaces face in substantially opposite directions and the first and second back surfaces face each other;
- a flame effect element positioned in at least one path of light between said at least one light source and the first and second screens respectively, the flame effect element being positioned at least partially between the first and second screens; and
- the flame effect element being adapted to configure light from said at least one light source to form said at least one image of flames transmittable through the front surfaces of the first and second screens respectively.

44. (Previously presented)

A flame simulating assembly according to claim 43 additionally comprising at least one flicker element positioned in said at least one path of light between said at least one light source and the flame effect element, for causing light from the light source to fluctuate.

45. (Previously presented)

A flame simulating assembly according to claim 43 in which the flame effect element comprises a body portion having a first side facing the first screen and a second side facing the second screen.

46. (Withdrawn)

47. (Withdrawn)

48. (Withdrawn)

49. (Withdrawn)

50. (Withdrawn)

51. (Withdrawn)

52. (Withdrawn)

53. (Withdrawn)

54. (Withdrawn)

55. (Withdrawn)

56. (Withdrawn)

57. (Withdrawn)

58. (Withdrawn)

59. (Withdrawn)

60. (Withdrawn)

61. (New)

A flame simulating assembly for providing at least one image of flames, the flame simulating assembly comprising:

at least one light source;

a first screen with a front surface;

the first screen being positioned in a first path of light from said at least one light source, the first screen being adapted to receive light from said at least one light source to form said at least one image of flames transmittable through the front surface of the first screen;

a second screen with a front surface;

the second screen being positioned in a second path of light from said at least one light source, the second screen being adapted to receive light from said at least one light source to form said at least one image of flames transmittable through the front surface of the second screen; and  
the first and second screens being disposed relative to each other such that the front surfaces thereof face in substantially opposite directions.